

CALL NOW +91 888 666 0 661

WWW.FLEETLY.IN

♥ UNIT #401, PSR PRIME TOWER, BESIDE DLF CYBER CITY GACHIBOWLI, HYDERABAD, TELANGANA 500032

COMPLIANT WITH AIS 140

PRODUCT DATASHEET

Specification

Internal

Dual Q DSP6 (600MHz)

Item

Core

Telecom Core

Cellular Module

GNSS Module

Antennae

Memory



Communication Interface TCP/IP Record Storage/buier 120000 Tracking Records. (may vary based on configuration and parameter chosen) **Ports** 1-USB Device type, 2 RS232, 1 CAN, 3 Analog Input, 5 Digital Inputs, 3 Digital Outputs GNSS(default), Real time(VSS Interface) Speed Sensor SIM Interface Supports SIM card: 1.8V & 3V / Embedded SIM (optional) **LED** Indication Processing, Cellular, G NSS, USB Detection Connectors 36 Pin power mate connector Wide DC input voltage range (9V - 32V) **Power Supply Current Consumption** 300mA(Max) during Transmission, 80mA during tracking, 20mA during Standby **Internal Battery** 700mah, 5 to 8 Hr backup, can be charged from USB interface /cable also

Enclosure Rugged IP 67 rated ABS Plastic Casing Operating: -20° C to +60° C Temperature Storage: -20° C to +85° C (Without Battery) Dimension 150 x 100 x 30 mm Weight 200 grams **FOTA** Firmware upgrade over the air available Other Interfaces Tamper Alert, Audio, 1Wire GeoF encing Polygonal G eo F encing available Connectivity Wifi(HotSpot), Bluetooth, Cellular